

# IMPULSE WRENCH 1/4 HEX 6-12,5NM

## RRI-30AT

The RED ROOSTER Impulse wrenches are handheld tools made for assembly with threaded fasteners. Impulse wrenches increase productivity. Typically meant for use in: Production of agricultural machinery, production of pumps, motors, bikes and any other serial production. The tool has a wide body air motor. Torque level adjustable in the impulse mechanism.

### Characteristics:

- Lightweight
- Free of reaction forces
- Low noise and vibration levels
- Powerful and fast
- High repeatability of the torque level
- Pistol model
- Auto shut off function

### Related products



RRI-9001/1

Spring balancer 0,5 -1,5 kg

### Related accessories



01-0505Y0

standard accessories kit



I40-109-A05

Protection Cover RRI-30/40/50(A/T)



61022-TH002

Tool Holder, diameter 47mm



ATLUB

Air Tool Oil, 1 litre



### Specifications

|                                           |                      |
|-------------------------------------------|----------------------|
| Brand                                     | RedRoosterIndustrial |
| Bolt capacity (mm)                        | 6                    |
| RPM                                       | 4600                 |
| Torque (Nm)                               | 6 - 12,5             |
| Airconsumption (l/s)                      | 3,7                  |
| Weight (kg)                               | 0,89                 |
| Hexagon                                   | 1/4"                 |
| Airconnection                             | PT 1/4"              |
| Airpress max. (MPa)                       | 0,63                 |
| mm A                                      | 163                  |
| mm B                                      | 168                  |
| mm C                                      | 46                   |
| mm D                                      | 21                   |
| mm E                                      | 17,5                 |
| Hosediameter (mm)                         | 6,5                  |
| Vibration standard                        | EN ISO 28927-2       |
| Vibration value (m/s <sup>2</sup> )       | 2,8                  |
| Vibration uncertainty (m/s <sup>2</sup> ) | 0,77                 |
| Sound standard                            | ISO 15744            |
| Sound pressure (dB(A))                    | 70,1                 |
| Sound uncertainty (dB(A))                 | 3                    |
| EAN                                       | 8717981203840        |

