

IMPACT WRENCH 3/4" MI-20PG

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-20GP is developed for assembly- and disassembly purposes. The Twin-Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and durable
- Clutch: Twin-Hammer
- Adjustable power, 4 positions
- Exhaust through isolated grip, with silencer

Related products



DO605421001

Impact Socket Set 3/4" deep 10-parts



DO605401001

Impact Socket Set 3/4" 10-parts

Related accessories



DOESR-2

Ret Ring



ATLUB

Air Tool Oil, 1 litre



DOESR-1

Ret Ring



Specifications

Brand	Toku
Square Drive	3/4"
Version	R+H
Bolt capacity (mm)	24
Impact mechanism	Twin-Hammer
RPM	5000
Torque (Nm)	1000
Force adjustment	R/L 4 standen
Airconsumption (l/s)	15
Weight (kg)	3,9
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	215
mm B	38
Hosediameter (mm)	10
Max. breakaway torque (Nm)	2400
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	8,5
Vibration uncertainty (m/s ²)	1,34
Sound standard	ISO 15744
Sound pressure (dB(A))	94
Sound power (dB(A))	105
Sound uncertainty (dB(A))	3
EAN	8717981380893

