

# AUTO-SHUT-OFF SCREWDRIVER 0,8~4,5NM

## RRI-SP21705

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

### Characteristics:

- New body-design
- Reversible
- Revolving rear-exhaust, silenced
- ergonomic grip
- easily adjustable

### Related products



TW-0

Spring Balancer 0,5-1,5kg

### Related accessories



61022-TH001

Tool Holder



00-4507

Torque Adjust Key RRI screwdriver



ATLUB

Air Tool Oil, 1 litre



### Specifications

|                                           |                      |
|-------------------------------------------|----------------------|
| Brand                                     | RedRoosterIndustrial |
| Bolt capacity (mm)                        | 3 ~ 4                |
| RPM                                       | 1700                 |
| Torque (Nm)                               | 0,8 ~ 4,5            |
| Airconsumption (l/s)                      | 11                   |
| Weight (kg)                               | 1,02                 |
| Hexagon                                   | 1/4"                 |
| Airconnection                             | PT 1/4"              |
| Airpress max. (MPa)                       | 0,63                 |
| mm A                                      | 208                  |
| mm B                                      | 16                   |
| mm C                                      | 166                  |
| mm D                                      | 37,2                 |
| Hosediameter (mm)                         | 6,5                  |
| Vibration standard                        | EN ISO 28927-2       |
| Vibration value (m/s <sup>2</sup> )       | <2,5                 |
| Vibration uncertainty (m/s <sup>2</sup> ) | 0,1                  |
| Sound standard                            | ISO 15744            |
| Sound pressure (dB(A))                    | 76                   |
| Sound uncertainty (dB(A))                 | 3                    |
| EAN                                       | 8717981428168        |

