DRILL 6-8 MM 2800 RPM
YRD-6NBK

This Yokota drill is suitable for industrial applications. The two-step trigger allows easy setting of the drill tip at first stage, and afterward high rpm for maximum drilling-speed.
Characteristics:
*** Compact and lightweight**
*** Low vibrationlevel**
*** Exhaust through grip, with silencer**
*** Ergonomic design**
*** Includes 10 mm key-less drill chuck**



Related accessories

766-027
Side Handle



775-041
Elastic Collar (📖 44)



766-025
Side Handle Frame



BHS-10MM
Drill Chuck (Quick Change) 3/8X24Nf



ATLUB
Air Tool Oil, 1 litre

Specifications

Brand	**Yokota**
RPM	**2800**
Airconsumption (l/s)	**8,3**
Weight (kg)	**0,90**
Drill chuck	**3/8" x 24UNF**
Capacity steel (mm)	**6 - 8**
Direction	**R**
Airconnection	**PT 1/4"**
Airpress max. (MPa)	**0,63**
mm A	**151**
mm B	**140**
mm C	**21**
Hosediameter (mm)	**10**
Power (kW)	**0,33**
Vibration standard	**EN ISO 28927-5**
Vibration value (m/s²)	**< 2,5**
Vibration uncertainty (m/s²)	**1**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**77**
Sound uncertainty (dB(A))	**3**
EAN	**8717981000678**

